

Cherokee Nation Code Annotated
Title 47: Motor Vehicles
Chapter 12: Equipment of Vehicles
Article IV. Other Equipment
§ 12-206.1. Turn signal lamps
Cite as: 47 CNCA § 12-206.1

A. Every vehicle shall be equipped with turn signal lamps that flash for the purpose of indicating the intention to turn either to the left or to the right.

B. The flashing turn signal lamps required by this section:

1. Shall show to the front and rear of the vehicle;
2. On the front of the vehicle, shall be located on the same level, as widely spaced laterally as practicable, at a height of not more than seventy-two (72) inches nor less than fifteen (15) inches, and when in use shall display a white or amber light, or any shade of color between white and amber, visible from a distance of not less than five hundred (500) feet to the front in normal sunlight; and
3. On the rear of the vehicle, shall be located at the same level and as widely spaced laterally as practicable, at a height of not more than seventy-two (72) inches nor less than fifteen (15) inches, and when in use shall display a red or amber light, or any shade of color between red and amber, visible from a distance of not less than five hundred (500) feet to the rear in normal sunlight.

C. A truck-tractor need not be equipped with turn signal lamps mounted on the rear if the turn signals at the front are so constructed and so located that they meet the requirements for double-faced turn signals that meet the standards of the Society of Automotive Engineers (SAE).

Historical Data

LA 02-21, eff. January 11, 2021.